

REVOIR IPARIS

ceramic tiles

RE-BEL

Gris rect

Collection: RE-BEL
Color: Gris
Top finish: Mat - R10
Size: 60 x 60cm & 100x100
Thickness: 9,5 mm & 10mm
Material Type: Porcelain - single firing - dry pressed ceramic tile



V-Shade : 2

TECHNICAL DATA

| | Standard test | Value required by UNE-EN-14411 | Average value |
|-------------------------------------------------------------------------------------------------------|------------------------------------------|----------------------------------|-----------------------------------------------|
| Dimensional features: | UNE-EN-ISO-10545-2 | | Conforms to the requisites |
| Water absorption: | UNE-EN-ISO-10545-3 | E<0.5% | Eb 0.1% |
| Bending strenght Modulus of rupture Breaking strenght | UNE-EN-ISO-10545-4 | >35Nw/mm ² >1300Nw | 44 Nw/mm ² 1923 Nw |
| Resistance to surface abrasion | UNE-EN-ISO-10545-7 | | PEI IV |
| Linear thermal expansion | UNE-EN-ISO-10545-8 | <9*10 ⁻⁶ /°C | Declared value |
| Thermal shock restistance | UNE-EN-ISO-10545-9 | Required | Stands the test |
| Cracking resistance | UNE-EN-ISO-10545-11 | Required | Stands the test |
| Frost restistance | UNE-EN-ISO-10545-12 | Required | Stands the test |
| Chemical restistance Domestic and swimming pool products Acids and alkalis of low concentration | UNE-EN-ISO-10545-13 | | Class A HA - LA |
| Resitance to stains | UNE-EN-ISO10545-14 | Min class 4 | 5 |
| Friction coeficient Pendulum Ramp DCOF | UNE-ENV-12633 DIN51130 ANSI A137.1 | Declared value | PTV 45 wet - class 2 Class B - R10 0.67 |
| Resistance to fire | Decision 96/603/CE | | Not apply |

CE MARKING



CE Declaration of performance:
N° 001VV2019